



Product: LED PANEL LIGHT
Input Voltage: AC100V-240V / DC24V
Dimensions: 1198mm x 598mm x 14mm

Item No.: TP-76-W-6012-G
Power Consumption: 76Watts

A. PHOTO AND DIMENSION (MM)



B. INSTALLATION METHODS




B. PARAMETERS

ITEMS	PARAMETERS
Input Voltage	AC100-240V
Power consumption	76W
Luminous Flux	4510 Lm(Cold white), 4330 Lm(Natural white), 3200 Lm(Warm white)
Luminosity (height @ 1 meter)	1042 Lux (Cold white), 906 Lux (Natural white), 710 Lux (Warm white)
Color available	Cold white/Warm white/Natural white/Red /Green/Blue/Yellow/Orange/RGB
Life time	>50,000 hours
Operating Temperature	-10 °C to +40°C
Storage Temperature	-20 °C to +60°C
Humidity Operating	10-80%
Humidity Storage	10-80%
Weight	9.5KGS/PCS
Dimensions	1198*598*14mm
IK Code	IK04
IP Code	IP41
Fixing Ways	In-built, Mounting, Suspending
Packing:	Inner Carton : 1320*685*80 mm (1pcs/ctn) Outer Carton : 1355*690*200 mm (2pcs/ctn)

D. ILLUMINATION TEST AND LIGHT DISTRIBUTION GRAPH

Item No. TP-76-W-6012-G		
Height (M)	Area Φ (M)	Illumination Intensity (Lux)
0.5	0.57	2475
1.0	1.09	1042
1.5	1.73	507
2.0	2.30	302
2.5	2.88	202
3.0	3.46	142
Beam angle: 60 degree		Color: Cold White





Shenzhen TheLEDLight Co., Ltd
The LED Light (China) Co., Limited

Tel: +86-755-29652010

Fax: +86-755-29652015

<http://www.theledlight.com.cn>

<http://www.ledpanellights.com>

sales@theledlight.com.cn

sales@ledpanellights.com

SHENZHEN. CHINA